

HIGH EFFICIENCY
LED GENERAL LIGHTS




AUROLITE LGL[®] 120 | 240

efficiently illuminating
your way

GRAH[®]
LED LIGHTING

TECHNICAL DATA



AUROLITE LGL®

120

120

240


Light source	120	120	240
	mid power LEDs by Lumileds		
Voltage	220 – 240 V (50 – 60 Hz)		
Driving current	350 mA	350 mA	2 x 350 mA
Power consumption	47 W	46 W	92 W
Luminaire flux	4,100 lm	3,100 lm	7,600 lm
Colour temperature	4000 K (5000 K on request)		
Lifetime	min 50.000 hours		
Ingress protection	IP20 (IP54 on request)		
Protection class	I		
Temperature range	-30 to +50 °C		
Operating temperature	+55 °C		
Material	Housing: aluminium		
	Cover: polycarbonate		
Housing colour	White		
Dimming	DALI (on request)		
Weight	5.70 kg	5.70 kg	11.40 kg
Product dimensions (LxWxH)	597 x 597 x 75	1197 x 297 x 75	1197 x 597 x 75



MOUNTING OPTIONS & LIGHT DISTRIBUTION

Mounting height: 3 - 4 m


Top ceiling



Flush ceiling



Symmetric, 4,100 lm



GRAH®
LED LIGHTING

LGL 120
LGL-120-01-F-00-XXX-NO-MP-XX-047-XX

This luminaire contains built-in LED lamps.

A+
A+
A
B
C
D
E

} LED

The lamps cannot be changed in the luminaire.

874/2012

Distributor

GRAH®
LED LIGHTING

www.grahlighting.com

Manufacturer reserves all rights to make changes in materials and components used in its products. All data are subject to change without prior notification.

efficiently
illuminating
your way